

Seqrite Endpoint Protection Cloud 5.0

Deploying EPP Clients via ManageEngine

Installation Steps

Copyright Information

Copyright © 2018–2024 Quick Heal Technologies Ltd. All Rights Reserved.

No part of this publication may be reproduced, duplicated, or modified in any form or incorporated into any information retrieval system, electronic or any other media or transmitted in any form without prior permission of Quick Heal Technologies Limited, Marvel Edge, Office No.7010 C & D, 7th Floor, Viman Nagar, Pune 411014, Maharashtra, India.

Marketing, distribution or use by anyone barring the people authorized by Quick Heal Technologies Ltd. is liable to legal prosecution.

Trademarks

Seqrite and DNAScan are registered trademarks of Quick Heal Technologies Ltd. while Microsoft and Windows are registered trademarks of Microsoft Corporation. Other brands and product titles are trademarks of their respective holders.

License Terms

Installation and usage of Seqrite Endpoint Protection is subject to user's unconditional acceptance of the Seqrite end-user license terms and conditions.

To read the license terms, visit <http://www.seqrite.com/eula> and check the End-User License Agreement for your product.

Contents

1. Overview.....	2
2. Audience.....	2
3. Prerequisites/System Requirements	2
4. Installation Steps.....	3
5. Windows.....	3
6. Mac.....	6
7. Linux	11

Overview

This document guides you with the steps to deploy End Point Protection clients using Manage Engine. Note that the steps mentioned in this document are one of the ways to deploy EPP client. While deploying, you can configure the settings to suit your requirement.

Audience

This guide is useful for the SEQRITE support or customer/partner system administrators who would be carrying out the deployment.

Prerequisites/System Requirements

Manage Engine - Install Agent should be deployed on the Endpoints.

Installation Steps

Windows

Windows Client


Follow these steps to download Windows client package:

1. Log in to EPP Console.
2. Go to the Deployment page.
3. Download the Windows Client installer (without AV) build package (Windows 32/64) from the Deployment page. These builds will be in the ZIP format.
4. Extract the .zip file containing clagnt.dat and clagnt64.exe files.


Windows Client Deployment with ManageEngine

Follow these steps to deploy Windows client using the Custom Script method:


1. Log in to the ManageEngine Endpoint Central Console.
2. Go to **Configuration > Windows**.



3. On Add Configuration page, click Custom Scripts.



4. The Custom Script page opens. Provide the following details:



- a. Name: For example, WinAVDeploy
 - b. Execute Script from/Run: Command Line
 - c. Command Line: clagnt64.exe /silent
 - d. Dependency File(s): Select the entire list of files present in the Windows Client extracted build package directory. For example, clagnt.dat and clagnt64.exe.
 - e. Frequency: Once
 - f. Ticket – Select **Enable Logging for Troubleshooting**
 - g. Define Target:
 - Remote Office/Domain: Workgroup
 - Filter Computer based on: Computer - Select Windows Client computer name.
5. Click **Deploy Immediately**.

Mac

Mac Client

Prerequisites

- Administrator must have an account on the Mac client computers with admin privileges.
- Enable Remote Management on the Mac client computers.
- Your administrator computer must have packages installed on it. Packages is a Mac OS application that helps you to create bundle for your payload and installation. To download packages, visit <http://s.sudre.free.fr/Software/Packages/about.html>.
- ManageEngine Agent should be installed on Mac device.
- Mac device should be enrolled with ManageEngine.
- For macOS Catalina and above only, do the following on your Mac system:
 - 1 Open **System Preferences**.
 - 2 Go to **Security & Privacy > Privacy** tab.
 - 3 Click the lock icon and provide password if it is locked.
 - 4 Select **Full Disk Access** in the left pane.
Add the following process in the given path and then select the processes in the Security & Privacy Full Disk Access window,
/Library/PrivilegedHelperTools/fr.whitebox.packages/packages_dispatcher

Steps

Follow these steps to create the Mac client package:

1. On the Seqrite Endpoint Protection, download UEMREMOTEINST.TAR from the URL.
Note: This tar file is common for EPP Cloud and NG Mac clients. It contains files which are required for creating Mac client packager.
<http://dlupdate.quickheal.com/builds/seqrite/uemcp/en/UEMREMOTEINST.tar>
2. Download Mac client installer from the EPP server. These builds will be in the TAR format
3. Rename the Mac client installer as follows:
 - **Mac client installer - MCCLAGNT.TAR**
4. Extract UEMREMOTEINST.TAR.
5. Copy MCCLAGNT.TAR to /UEMREMOTEINST.

6. Open Terminal.app with user having administrative privileges on the Mac computer and go to the UEMREMOTEINST folder.

Enter the following commands:

- **cd ./Remote_Installation/PKG**
- **sudo sh ./ClientAgentInstaller/CreatePackage.sh**

When the package creation is completed successfully, ClientAgentInstaller.pkg file is created in the ./Remote_Installation/PKG/ClientAgentInstaller/ folder.

Note: Use this **ClientAgentInstaller.pkg** for Mac client deployment using ManageEngine Endpoint Central.

Deploying Profile

Follow these steps to deploy profile with ManageEngine to load product extensions silently and to provide full disk access:

1. Log in to the Manage Endpoint Central Console.
2. Go to **Configuration** and select **Mac**.
3. Select **Custom Configuration**.
4. Enter custom configuration name.
5. Download the profile from
<http://download.quickheal.com/builds/seqrite/50/en/build/SeqriteMacProfile.zip>
Extract the downloaded SeqriteMacProfile.zip, it will contain
SeqriteMacProfile10.12.mobileconfig
6. Click **Browse**. The downloaded **SeqriteMacProfile10.12.mobileconfig** into the **Custom Configuration profile**.
Note: This profile will work on macOS Big Sur and onwards systems.
7. Define Target:
 - a. Remote Office/Domain: Select the domain name.
 - b. Filter Computer based on: Computer - Select Mac Computer name. (You can find Mac Computer name at > click ellipse> Click 'Agent' > Click 'Mac' chart from OS Platform.)
8. Click **Deploy** Immediately.

Mac Client Deployment with ManageEngine

1. Log in to the Manage Endpoint Central Console.
2. Go to Software Deployment.

Endpoint Central Home Configurations Threats & Patches **Software Deployment** Inventory OS Deployment Mobile Device Mgmt. ... Jump to SDP

Package creation
Packages
Templates

Deployment
Install/Uninstall Software >
View Configurations
User-defined Templates
Trash
Self Service Portal

Reports
Self Service Portal Reports
SSP Usage Reports

Settings
Software Repository

Sync Application Details
Sync Now
Last Update: Oct 31, 2023 05:22 PM

Unpublished packages in SSP 9

Packages in SSP which are not in use 0

Watch Demo Need to deploy software to other Linux OS's?

Filter By: Mac Commercial Mac

+ Add Package x Delete Packages Install/Uninstall Software Mark License Type

Package Name	Software Name	Created By	Modified Time	Auto-update status	Platform	Action
Mac_Package	--	admin	Oct 25, 2023 12:17 PM	Not Applicable	Apple Mac	...

Total: 1 | Q | 25

© 2023 Zoho Corporation Private Limited. All rights reserved.

3. Click Add Package. Select Mac from the drop-down values.

Endpoint Central Home Configurations Threats & Patches **Software Deployment** Inventory OS Deployment ... Jump to SDP

Package creation
Packages
Templates

Deployment
Install/Uninstall Software >
View Configurations
User-defined Templates
Trash
Self Service Portal

Reports
Self Service Portal Reports
SSP Usage Reports

Settings
Software Repository

Sync Application Details
Sync Now
Last Update: Oct 31, 2023 05:22 PM

Unpublished packages in SSP 9

Packages in SSP which are not in use 0

Watch Demo Need to deploy software to other Linux OS's?

Filter By: Package Type License Type Platform

+ Add Package x Delete Packages Install/Uninstall Software Mark License Type


- Windows
- Mac

Package Name	Software Name	Created By	Modified Time	Auto-update status	Platform	Action
Windows	--	admin	Oct 20, 2023 10:16 PM	Not Applicable	Windows	...
Mac	--	admin	Oct 20, 2023 10:12 PM	Not Applicable	Windows	...
EPS_x64	--	admin	Oct 20, 2023 10:12 PM	Not Applicable	Windows	...
Google Chrome (x64) L...	Google Chrome	admin	Oct 20, 2023 07:32 PM	Not Enabled	Windows	...


Total: 9 | Q | 25

© 2023 Zoho Corporation Private Limited. All rights reserved.


4. Enter the **Package Name**.



5. Select **Commercial** from the **License Type** drop-down values.
6. Click **Browse** to upload the Mac packager that is, **ClientAgentInstaller.pkg**.
7. Click **Add Package**. The packager gets added.
8. Now, in the left pane, go to **Deployment > Install/Uninstall Software > Mac > Computer Configuration**.



9. Give an appropriate name for configuration.



10. Select Operation Type: **Install**.

11. Select the package name that you entered earlier from the Package Name drop-down list values.

12. Select **Deploy any time at the earliest** from Apply Deployment Policy drop-down list values.

13. Define Target:

a. Remote Office/Domain: Select the domain name.

b. Filter Computer based on: Computer - Select Mac Computer name. (You can find Mac Computer name at > click ellipse> Click 'Agent' > Click 'Mac' chart from OS Platform.)

14. Click **Deploy** Immediately.

Linux

Linux Client

Follow these steps to download Linux client package:

1. Log in to EPP Console. Go to the Deployment page.
2. Download the Linux Client installer build package (Linux 32/64) from the Deployment page. These builds will be in the TAR format.
3. Extract the .tar file containing buildNumber.txt, clagnt.dat, epslin64.tar.gz, install, readme.txt, and validation files.
4. Rename the install script file as **install.sh**.

Linux Client Deployment with ManageEngine:

Follow these steps to deploy the Linux client using Custom Script method:

1. Log in to the Manage Endpoint Central Console.
2. Go to **Configuration > Linux**.
3. On **Add Configuration** page, click **Custom Script**.

4. On the Custom Script page, enter the following details:

The screenshot shows the 'Custom Script (Computer)' configuration page in Endpoint Central. The 'Name' field is filled with 'MyConfiguration95'. Under 'Configure Custom Script', 'Execute Script from / Run' is set to 'Command Line'. The 'Command Line' field is empty. 'Dependency Files(s)' has a 'Choose files (or) Drop here' button and a 'Browse' button. 'Specify the exit code(s)' is set to '0'. 'Frequency' is set to 'Once'. 'Enable Logging for Troubleshooting' is unchecked. Under 'Define Target', 'Target 1' is set to 'Remote Office/Domain'. Under 'Execution Settings: [Optional]', 'Retry this configuration on failed targets' and 'Enable Notification' are both unchecked. At the bottom, there are buttons for 'Deploy', 'Deploy Immediately', 'Save As', and 'Cancel'.

- Provide Name: For example, LinAVDeploy
- Execute Script from/Run: Command Line
- Command Line: `bash install.sh`
- Dependency File(s): Select the entire list of files present in the Linux client extracted build package directory. For example, `buildNumber.txt`, `clagnt.dat`, `epsln64.tar.gz`, `install.sh`, `readme.txt`, `validation`.
- Frequency: Once
- Ticket - Enable Logging for Troubleshooting
- Define Target:
 - Remote Office/Domain: Workgroup
 - Filter Computer based on: Computer - Select Linux Client host name.

5. Click **Deploy Immediately**.